

Set bolt for alignment adjustment

**ProAction™ Technology**

design is **Patent Pending**.  
Graphite impregnated nylon roller – precision turned with exclusive tapered side walls virtually eliminate the sidewall drag and rubbing found on other square frame gate rollers.

Full  $\phi$  7" diameter with a 4000lb reaction load rating.

1.34"  
(34mm)

5/16" (8mm) galvanized steel bracket with 0.5" thick axle housing gusseted 3 ways

$\phi$ 1.125" Axle  
(28mm)

Axle Cap

Stainless Snap Ring (2)

Nylon Dust Cover (2)

Permanently Lubricated Sealed Bearings (2)

UV Stabilized cover is pre-installed and meets ASTM 2200 requirements

2" gate frame by others

**ProAction™**  
Patent Pending Design - virtually eliminates side wall drag.

4" Square Post (by others)

4.41"  $\pm$ 0.08"  
(112mm  $\pm$ 2)

Subject to change without notice  
Effective January 2, 2012  
© Larsen Innovations LLC 2012  
Patent Pending



**LARSEN INNOVATIONS LLC**

618 10th Street, Huntington Beach, CA 92648  
www.LarsenInnovations.com  
info@LarsenInnovations.com

**Accura™ 30854 External Nylon Cantilever**

**ProAction™ SQ Gate Roller** (Gates & Posts by others - no scale)

Project:

Submitted by: